

Printing date 10/29/2024 Reviewed on 10/29/2024

1 Identification

- · Product identifier
- · Trade name: UltraSeal XTTM Plus
- · Article number: SDS 25-001.17R01, 13560, 56303, 10952, 73401
- · Application of the substance / the mixture Professional Dental Pit and Fissure Sealant
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

onlineordersupport@ultradent.com

- · Information department: Customer Service
- · Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS07

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements Void
- · Hazard pictograms GHS07
- · Signal word Warning
- · Health Hazard-determining components of labeling:

Triethylene Glycol Dimethacrylate

Diurethane Dimethacrylate

2-Hydroxyethyl Methacrylate

Trade Secret

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/29/2024 Reviewed on 10/29/2024

Trade name: UltraSeal XTTM Plus

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



0 Health = 0Fire = 1

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
109-16-0	Triethylene Glycol Dimethacrylate	>10-≤25%
72869-86-4	Diurethane Dimethacrylate	1-10%
868-77-9	2-Hydroxyethyl Methacrylate	≥0.1-<1%
	Trade Secret	≥0.1-<1%

Additional information:

The specific chemical identity of composition is being withheld as a trade secret. The specific chemical identity is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of paragraph §1910.1200.

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If swallowed in large quantities seek medical attention.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Foam, dry chemical, carbon dioxide

Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 10/29/2024 Reviewed on 10/29/2024

Trade name: UltraSeal XTTM Plus

(Contd. of page 2)

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid contact with eyes, skin, and clothing. Use suitable protective equipment.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: See product labeling.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: See product labelling.
- · Specific end use(s) Professional Dental Pit and Fissure Sealant

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/29/2024 Reviewed on 10/29/2024

Trade name: UltraSeal XTTM Plus

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material is based on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling.
- · Body protection: Protective work clothing

9 Physical and chemical properties		
· Information on basic physical and · General Information	chemical properties	
· Appearance:	M 1: II: 1 IV:	
Form: Color:	Medium-High Viscosity Liquid	
· Odor:	Shade dependent Acrylic	
· Odor: · Odor threshold:	Not determined.	
· Ouor inresnoia.	Noi determined.	
· pH-value:	Not applicable (non-aqueous)	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined	
· Flash point:	>100 °C	
· Flammability:	Not applicable.	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C:	0 hPa	
Density at 20 °C:	1.7-1.8 g/cm³	
· Relative density	Not determined	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
		(Contd. on page 5)

(Contd. on page 5)

Printing date 10/29/2024 Reviewed on 10/29/2024

Trade name: UltraSeal XTTM Plus

		(Contd. of page 4
· Solubility in / Miscibility with		
Water:	Partly miscible.	
· Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Avoid light exposure
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

	values that are relevant j Triethylene Glycol Dime	•
	· · · ·	
Oral	LD50	>5,000 mg/kg (rat)
	LC50 Fish	16.4 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (mouse)
72869-86	-4 Diurethane Dimethacı	rylate
Oral	LD50	>5,000 mg/kg (rat)
868-77-9	2-Hydroxyethyl Methacr	ylate
Oral	LD50	3,275 mg/kg (mouse)
		>5,000 mg/kg (rat)
	LC50 Fish	>100 mg/l (Fish)
Dermal	LD50	>3,000 mg/kg (rabbit)
	LC50(Daphnia magna)	24.1 mg/l (daphnia)
Trade Sec	eret	
Oral	LD50	1,550 mg/kg (rat)
	LC50 Fish	19 mg/l (Fish)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	96 mg/l (rat)

- Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.

(Contd. on page 6)

Printing date 10/29/2024 Reviewed on 10/29/2024

Trade name: UltraSeal XTTM Plus

(Contd. of page 5)

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

Toxicity				
· Aquatic toxicity:				
109-16-0 Triethyl	109-16-0 Triethylene Glycol Dimethacrylate			
EC50	>100 mg/kg (Algae)			
Biodegradability	28 days (Aerobic) (Biodegradability testing)			
Aqua toxicity	32 mg/l (daphnia) (No Observed Effect Concentration)			
72869-86-4 Diure	72869-86-4 Diurethane Dimethacrylate			
EC50	>0.6 mg/kg (Algae)			
Biodegradability	28 days (Aerobic) (Biodegradability testing)			
868-77-9 2-Hydro	868-77-9 2-Hydroxyethyl Methacrylate			
EC50	345 mg/kg (Algae)			
Trade Secret	Trade Secret			
EC50	42 mg/kg (Algae)			

- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Disposal should be in accordance with applicable regional, national and local laws and regulations. Dispose of contents/container in accordance with international, federal, state, and local regulations.

(Contd. on page 7)

Printing date 10/29/2024 Reviewed on 10/29/2024

Trade name: UltraSeal XTTM Plus

(Contd. of page 6)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	N (D 1 (I	
DOT, ADN, IMDG, IATA	Not Regulated	
UN proper shipping name DOT, ADN, IMDG, IATA	Not Regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	Not Regulated	
Packing group		
DOT, IMDG, IATA	Not Regulated	
Environmental hazards:	Not Applicable.	
Special precautions for user	Not Applicable	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not Applicable.	
UN "Model Regulation":	Not Regulated	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Sara		
· Section 355	(extremely hazardous substances):	
None of the	ingredients is listed.	
· Section 313	(Specific toxic chemical listings):	
Trade Secre	t	
· TSCA (Tox	ic Substances Control Act):	
109-16-0	Triethylene Glycol Dimethacrylate	ACTIVE
	Diurethane Dimethacrylate	ACTIVE
868-77-9	2-Hydroxyethyl Methacrylate	ACTIVE
	Trade Secret	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 8)

Printing date 10/29/2024 Reviewed on 10/29/2024

Trade name: UltraSeal XTTM Plus

(Contd. of page 7)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· ACGIH Carcinogenicity (American Conference of Governmental Industrial Hygienists)

Trade Secret A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health, and Safety
- · Contact: Customer Service
- · Date of preparation / last revision 10/29/2024 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Sensitization - Skin 1: Skin sensitisation - Category 1

* Data compared to the previous version altered.

- IIS